



TECHNICAL SPECIFICATION

<b>Product Code</b>		<b>7628-1</b>	
<b>Description</b>		Woven Glass Fibre (Contains No Asbestos)	
<b>Colour</b>		White	
<b>Weave</b>		Plain	
<b>Yarn</b>	<b>Warp</b>	EC9 33 2X1	ECG 150 2/1
	<b>Weft</b>	EC9 33 2X1	ECG 150 2/1
<b>Tex</b>			
<b>Width</b>		100 Cm	40 Inch
<b>Thickness</b>		0.20 mm	0.0079 Inch
<b>Weight</b>		200 G/SQM	5.80 OZ/SQ Yard
<b>Thread</b>	<b>Warp</b>	17 Per Cm	43 Per Inch
	<b>Weft</b>	12 Per Cm	33 Per Inch
<b>Count</b>			
<b>Tensile</b>	<b>Warp</b>	2025 N/5 Cm	225 Lbs/Inch
	<b>Weft</b>	1620 N/5 Cm	180 Lbs/Inch
<b>Strength</b>			
<b>L.O.I %</b>		<0.1%	
<b>Service Temperature</b>		550°C	
<b>Application</b>		This Material is Suitable for Heat Insulation, Protection Against Weldin Spark & Light Welding Spatter.	